

Fact Sheet

PostBase[™] Vision



Features

- Easy to use large, 5" color touchscreen
- Motorized, tilting display for best viewing angle
- Automatic envelope processing at up to 50 letters/minute
- SealCheck envelope sealing security
- Sealing status light indicator
- I0 lb. capacity integrated postal scale
- Differential weighing for integrated scale
- Rate wizard for USPS[®] postal products
- Automatic USPS[®] postal rate updates
- Integrated postage tape dispenser for parcels
- Supports USPS[®] DIM rating
- Secure PIN protection
- 10 customizable rate shortcuts
- 6 standard printable envelope graphics/adverts
- Op to 30 custom printable envelope graphics
- Create up to 12 different printable text messages or QR codes to promote your mail
- Received stamp for incoming mail
- Easiest ink replacement with on-screen guidance
- Connected to discover FP for easy mailing system management

Options & Upgrades

- Integrated scale capacity upgrade to 15 lbs.
- Large platform external scale up to 70 lbs.
- Vision360 online postal analytics and reporting for up to 250 cost accounts
- FP Parcel Shipping
- Choose from 5 designer colors (Satin Steel/Black std.)



Satin Steel - Cashmere Blue - Marble White - Sahara Gold - NBCF® Pink

Specifications

- Dimensions: 37"(L) x 16"(D) x 11.3-12.9"(H)
- Expandable Catch Tray Length: 12.6"-17.5"
- System Weight: 48.3 lbs.
- Catch Tray Weight: 2.2 lbs.
- Envelope Sizes: 4" x 6" 10" x 14"
- Maximum Envelope Thickness: .40"
- Noise Emission: <70 dB(A)

Connectivity

• High-Speed LAN or Built-in Wi-Fi

Supplies

- USPS® Certified **FP** Postal Inkjet Cartridge
- Postage Meter Strip Tapes
- SEALIT Envelope Sealing Fluid

Postal Security Device (PSD/Meter)

- USPS[®] IMI Approved (Highest Level)
- FIPS 140-2 Level 3 Cryptography Certified

Manufacturing & Certifications

- Manufactured: Wittenberge, Germany
- ISO-9001, 14001, 45001, 50001, 27001
- CE, GS, CSA, Nemko, UL Listed
- Complies with FCC Part 15, Subpart B, Class B

Energy Consumption & Conservation

- Operating Energy Consumption: 80W
- Standby Energy Consumption: 7W
- Switched Off Energy: 0.5W
- Electrical Requirements: 100-240V/2.0A/50-60Hz
- Energy Star® 2.0 Certified



© 2019 FP Mailing Solutions. All Rights Reserved. TM, SM and ® denote trademarks or registered trademarks of Francotyp-Postalia, Inc. The FP logo and FP Mailing Solutions Product logos are trademarks or registered trademarks of Francotyp-Postalia, Inc.

www.fp-usa.com