

# Xerox® PrimeLink® C9065/C9070 Printer



Meet the Xerox® PrimeLink C9065/C9070. Engineered to make a great first impression, these intuitive printers come complete with spot-on color fidelity, best-in-class media latitude and professional finishing capabilities.

SYSTEM SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070	
SIMPLEX SPEEDS	COLOR	BLACK-AND-WHITE	COLOR	BLACK-AND-WHITE
<b>8.5 x 11 in. / A4</b> 60 to 105 gsm uncoated 106 to 176 gsm coated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 70 ppm Up to 70 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
<b>11 x 17 in. / A3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 35 ppm Up to 35 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
<b>12 x 18 in. / SRA3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 30 ppm Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm

# Xerox® PrimeLink® C9065/C9070 Printer

<b>AUTO DUPLEX SPEEDS</b>	<b>COLOR</b>	<b>BLACK-AND-WHITE</b>	<b>COLOR</b>	<b>BLACK-AND-WHITE</b>
<b>8.5 x 11 in. / A4</b> Example: 60 to 105 gsm uncoated	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 37 sheets per minute
<b>11 x 17 in. / A3</b> Example: 60 to 105 gsm uncoated	Up to 32 ipm 2-sided 16 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 37 ipm 2-sided 18 sheets per minute
<b>Monthly Duty Cycle</b>	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). <sup>1</sup>			
<b>Average Monthly Print Volume (AMPV)</b>	10,000 to 60,000 pages per month <sup>2</sup>			
<b>Technology</b>	Xerox® EA-Eco toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
<b>Control Panel Languages</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			
<b>ACCESSORIES</b>				
<b>Optional</b>	Xerox® EX-c C9065/C9070 Print Server Powered by Fiery® Xerox® EX-i C9065/C9070 Print Server Powered by Fiery® Xerox® EX C9065/C9070 Print Server Powered by Fiery® Simple Catch Tray (Europe only) Offset Catch Tray High Capacity Feeder (A4) 1-Tray Oversized High Capacity Feeder with Storage Cabinet 2-Tray Oversized High Capacity Feeder Interface Decurler Module Xerox® Business Ready Finisher (requires a Vertical Transport Kit) Xerox® Business Ready Finisher Booklet Maker (requires a Vertical Transport Kit) Xerox® Production Ready Finisher (requires Interface Decurler Module) Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module) Xerox® Production Ready Finisher Plus (includes PFIM Partner Finishing Interface Module; requires Interface Decurler Module) XLS Extension Tray Kits Plockmatic Pro50/35™ Booklet Maker Xerox® C/Z Folder Xerox® Basic Punch GBC® AdvancedPunch™ Pro Xerox® Crease/Two-sided Trimmer Xerox® SquareFold® Trimmer Module Xerox® Inserter Convenience Stapler Foreign Device Interface Kit Mobility Plate PostScript Kit VOIP Fax (SW) Kit Fax Kits (1 or 3 Line; requires fax installation kit) Server Fax Kit SIPRNET Kit Extension Long Smart Card Enablement Kit Integrated RFID Card Reader Kit (external)			

<b>ELECTRICAL REQUIREMENTS</b>			
<b>North America</b>	Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A		
<b>Europe</b>	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
<b>Accessories</b> North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
<b>POWER CONSUMPTION</b>			
<b>Running (Average)</b>	PrimeLink C9065: 1,052 watts; PrimeLink C9070: 1,250 watts		
<b>Sleep Mode (Average)</b>	3 watts (Default time to Sleep mode = 1 min.)		
<b>Low Power Mode Recovery Time</b>	Less than 20 seconds		
<b>OPERATING ENVIRONMENT</b>			
<b>Required Temperature Range</b>	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
<b>Required Relative Humidity</b>	15% to 85% (no condensation)		
<b>Sound Power Levels</b>	Operating: 6.8 B(A); Standby: 3.6 B(A)		
<b>Sound Pressure Levels</b>	Operating: 56 dB(A); Standby: 18 dB(A)		
<b>Weight (approximate base unit only)</b>	604 lb., 273 kg		
<b>DIMENSIONS</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>
<b>Base Unit w/ Offset Catch Tray</b>	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Base Unit w/ Business Ready Finisher</b>	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Base Unit w/ Business Ready Booklet Maker Finisher</b>	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Base Unit w/ Business Ready Booklet Maker Finisher and C Fold / Z Fold Unit</b>	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Base Unit w/ Production Ready Finisher</b>	83.48 in. / 2,120.63 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Base Unit w/ Production Ready Booklet Maker Finisher</b>	94.46 in. / 2,399.43 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
<b>Xerox® Crease/Two-sided Trimmer</b>	23.81 in. / 760.5 mm	28.12 in. / 714.3 mm	39.03 in. / 991.5 mm
<b>Interface Decurler Module</b>	13.38 in. / 340 mm	28.51 in. / 724.3 mm	39.03 in. / 991.5 mm
<b>Xerox® SquareFold® Trimmer</b>	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm
<b>High Capacity Feeder</b>	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm

Xerox® PrimeLink® C9065/C9070 Printer

<b>One Tray Oversized High Capacity Feeder</b>	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
<b>Two Tray Oversized High Capacity Feeder</b>	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
<b>CERTIFICATIONS</b> To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			
<b>Graphic Arts Credentials</b>	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ IDEAlliance Digital Press Certified* to GRACoL® specifications *requires an additional Print Server option		
<b>PAPER HANDLING</b>			
<b>SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF) - NETWORK SCANNING</b>			
<b>Capacity<sup>3</sup></b>	250 sheets of plain paper – 20 lb. / 75 gsm		
<b>Speed</b>	Up to 270 ipm color / 270 ipm black-and-white (2-sided, 8.5 x 11 in. / A4)		
<b>Paper Sizes</b>	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A6 to A3		
<b>Weights</b>	16 to 53 lb. bond / 38 to 200 gsm		
<b>TRAY 5 (BYPASS)</b>			
<b>Capacity<sup>3</sup></b>	Up to 250 sheets		
<b>Sizes</b>	Custom sizes: 4 x 6 in. to 13 x 26 in. / 100 x 148 mm to 330.2 x 660 mm (A5 to SRA3) XLS sheet size: Up to 13 x 26 in. (330 x 660 mm)		
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 350 gsm (60 to 350 gsm uncoated; 106 to 350 gsm coated); XLS sheet: 60-220 gsm uncoated/106 to 220 gsm coated. Limit XLS in Bypass (Tray 5) to 5 or less sheets.		
<b>Envelope Capacity</b>	30 to 50 envelopes		
<b>Envelope Sizes</b>	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass). Paper Size Default within tools. Run flap open at the trail edge). Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in./ 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended.		
<b>Envelope Weights</b>	75 to 90 gsm		
<b>TRAYS 1 TO 4</b>			
<b>Capacity<sup>3</sup></b>	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets		
<b>Sizes</b>	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4		
<b>Weights</b>	Trays 1 and 2: 16 lb. bond to 94 lb. cover / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) Trays 3 and 4: 16 lb. bond to 80 lb. cover / 60 to 220 gsm (60 to 220 gsm uncoated; 106 to 220 gsm coated)		

<b>OPTIONAL HIGH CAPACITY FEEDER (HCF)</b>	
<b>Capacity<sup>3</sup></b>	2,000 sheets
<b>Sizes</b>	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 220 gsm (uncoated and coated)
<b>OPTIONAL OVERSIZED HIGH CAPACITY FEEDER (OHCF) – 1 OR 2 TRAY OPTIONS</b>	
<b>Capacity<sup>3</sup></b>	1 Tray OHCF: 2,000 sheets with Storage Cabinet 2 Tray OHCF: 4,000 sheets Tray 5 (Bypass): Up to 250 sheets; XLS capacity varies by media.
<b>Sizes</b>	1 Tray OHCF: Tray 6: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330x488 mm 2 Tray OHCF: Tray 6 and 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330x488 mm Custom sizes via Tray 5 (Bypass): 4 x 6 in. to 13 x 26 in. (XLS) / 100 x 148 mm to 330 x 660mm (XLS)
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 350 gsm (uncoated and coated); XLS: 60-220 gsm
<b>TOTAL CAPACITY</b>	
<b>Standard Capacity</b>	3,260 sheets (includes Tray 5 (Bypass) and Trays 1-4)
<b>Maximum Capacity</b>	7,260 sheets (includes Tray 5 (Bypass), Trays 1-4 and Two-tray Oversized High Capacity Feeder)
<b>Two-Sided</b>	94 lb. cover / 256 gsm auto duplex 129 lb. cover / 350 gsm manual duplex for all stocks from Tray 5 (Bypass) and optional Oversized High Capacity Feeder
<b>FINISHING</b>	
<b>OFFSET CATCH TRAY</b>	
<b>Capacity<sup>3</sup></b>	Up to 500-sheet stacking
<b>Simple Catch Tray (Europe only)</b>	Up to 500-sheet stacking
<b>OPTIONAL BUSINESS READY FINISHER</b>	
<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11 x 17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 350gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4 and B5 sizes supported
<b>Hole Punch</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)

<b>OPTIONAL BUSINESS READY BOOKLET MAKER FINISHER</b>	
<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking XLS output quantity is limited. Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
<b>Sizes</b>	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Booklet Maker
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, A4 Cover, Executive, 8 x 10 in., 8.5 x 13 in., 11 x 15 in., 215 x 315 mm, B4 and B5 sizes supported
<b>Hole Punch</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, B4, B5, Executive, 8.5x13 in., 11x15 in., 215x315 mm, 12 x 18 in., 13x18 in., SRA3 supported
<b>OPTIONAL C/Z FOLDER UNIT FOR BUSINESS READY FINISHER</b>	
<b>Types</b>	C Fold, Z Fold and Z Half Fold
<b>Capacity<sup>3</sup></b>	40 sheets
<b>Sizes</b>	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
<b>Weights</b>	16 to 24 lb. bond / 60 to 90 gsm
<b>Output Tray</b>	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
<b>OPTIONAL PRODUCTION READY FINISHER (REQUIRES INTERFACE DECURLER MODULE)</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Stacker Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 13 x 26 in. / A6 to SRA3
<b>Weights</b>	16 lb. bond to 129 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 16 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
<b>Multiposition Stapling</b>	Up to 100 sheets of 20 lb. bond / 80 gsm
<b>Hole-punching</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
<b>Inserter</b> Capacity: Sizes: Weights:	200 sheets of 126 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in., / A3, A4, B4, B5 18 lb. bond to 130 lb. cover / 64 to 350 gsm
<b>Decurling</b>	Included with Interface Decurler Module and Standard Finisher Bidirectional with Auto and Manual settings

<b>OPTIONAL PRODUCTION READY FINISHER WITH BOOKLET MAKER (REQUIRES INTERFACE DECURLER MODULE)</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Stacker Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
<b>Sizes</b>	4 x 6 in. to 13 x 19 in. / A6 to SRA3
<b>Weights</b>	18 lb. bond to 129 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 18 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray 18 lb. bond to 94 lb. cover / 60 to 256 gsm (coated and uncoated) Booklet Maker
<b>Multi-position Stapling</b>	Up to 100 sheets of 20 lb. bond / 80 gsm
<b>Hole-punching</b> North America: Europe:	2-3 Hole Punch (Optional) 2-4 Hole Punch (Optional) 4 Hole Swedish Punch (Optional)
<b>Inserter</b> Capacity: Sizes: Weights:	200 sheets of 128 gsm 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 11 x 17 in., / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
<b>Decurling</b>	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
<b>Booklet Making Capacity</b>	Saddle-stitch 2 to 30 sheets of 90 gsm (uncoated) or up to 15 sheets of 120gsm (coated); Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
<b>OPTIONAL PRODUCTION READY FINISHER PLUS (REQUIRES INTERFACE DECURLER MODULE)</b>	
	Provides same function as the Production Ready Finisher with a 500-sheet top tray and 2,000-sheet stacker tray. Used to connect third-party inline finishing options. Includes PFIM Partner Finishing Interface Module.
<b>OPTIONAL XEROX® CREASE AND TWO-SIDED TRIMMER</b>	
<b>Sizes</b>	Crease: 7.25 x 10.5 to 13 x 19 in. / A4 to SRA3, custom sizes 7.2 x 8.3 to 13 x 19 in. / 182 x 210 to 330 x 488 mm Trim: 8 x 10 to 13 x 19 in. / A4 to SRA3, custom sizes 7.2 x 10 to 13 x 19 in. / 182 x 257 x 330 x 488 mm
<b>Weights</b>	Crease: 18 lb bond to 129 lb cover / 60 to 350 gsm Trim: 18 lb bond to 129 lb cover / 60 to 350 gsm
<b>OPTIONAL GBC® ADVANCEDPUNCH PRO</b>	
<b>Punch Configuration Sizes</b>	A3, A4, A5, SRA3, 8.5 x 11 in., 8.5 x 14in., 11 x 17 in., 12 x 18 in.
<b>Weights</b>	20 lb. bond to 129 lb. cover / 75 to 350 gsm (uncoated); 28 lb. bond to 129 lb. cover / 106 to 350 gsm (coated)
<b>Dies</b>	Wide selection of slide-in / slide-out GBC punch die sets available
<b>Note:</b> When printing XLS with the GBC® AdvancedPunch PRO, the Xerox Inserter must be included in the system configuration	
<b>OPTIONAL XEROX® SQUAREFOLD® TRIMMER MODULE</b>	
<b>Capacity</b>	Up to 30 sheets of 90gsm
<b>Sizes</b>	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
<b>Weights</b>	18 lb. bond to 94 lb. cover / 64 to 220 gsm
<b>OPTIONAL CONVENIENCE STAPLER</b>	
<b>Capacity</b>	50 sheets (24 lb. / 90 gsm media)

<p><b>Extra Long Sheets (XLS) Finishing Limitations</b></p> <p>XLS will output to SCT, OCT, Business Ready Top Tray, and Production Ready Top Tray, however stacking quality will be limited. XLS Extension Tray Kit is available for the Production Ready Finisher to improve stacking of multiple sheets.</p> <p>When printing XLS with the GBC® AdvancedPunch PRO, the Xerox Inserter must be included in the system configuration.</p>	
<p><b>PRINT</b></p>	
<b>Print Resolution</b>	Up to 2400 x 2400 dpi
<b>Line Screens</b>	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
<b>Registration</b>	<ul style="list-style-type: none"> <li>• Advanced registration technology for tighter control</li> <li>• Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations as a Maintenance Tool: Alignment Adjustment)</li> </ul> <p>Up to 1.5mm. Variation will occur based on paper size, tray, etc.</p>
<b>First-Print-Out Time</b>	PS-A4 LEF Simplex Color 10.4 seconds / Black-and-white 8.5 seconds
<b>Print Drivers</b>	Xerox® Smart Start Driver Installer, Xerox® Global Print Driver® For information about supported print drivers please visit our Drivers & Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a> .
<p><b>PRINT SOLUTIONS</b></p>	
<b>Mobile Printing</b>	Apple® AirPrint®, Google Cloud Print™ Ready, Mopria® Print Service Plug-in for Android, Xerox® @PrintByXerox App, Xerox® Workplace Cloud/Suite Mobile Print Solution. Learn more at <a href="http://www.xerox.com/MobileSolutions">http://www.xerox.com/MobileSolutions</a> .
<p><b>COPY</b></p>	
<b>First-Copy-Out Time</b> From the Platen: From the DADF:	As fast as 7.8 seconds color / 5.1 seconds black-and-white As fast as 9.6 seconds color / 5.3 seconds black-and-white
<b>Warm Up Time</b>	90 seconds (from cold powered down to Ready Copy)
<b>Digital Imaging</b>	<p>Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) Lighter/Darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation</p>
<b>Reduce / Enlarge</b>	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
<b>Special Features</b>	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto color selection Area designation Poster mode Annotation Single/Dual color</p>



Xerox® PrimeLink® C9065/C9070 Printer

	<p>Booklet creation  Multi-up – 2, 4 or 8 up  Repeat image  Negative image  Mirror image  Covers insertion (front only, front and back, back only, blank or printed)  Build job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder)  Job interrupt  Book copying  Sample job  Mixed-size originals  Sheet insert  Stamping/Bates  2-in-1  X Y zoom  Zoom range 25 to 400 %  Margin shift  Photo Mode  Poster Mode  Preset Reduce / Enlarge  Program ahead  Covers  Erase, Image Repeat, Image Rotate  Interrupt</p>
<b>SCAN</b>	
<b>Concurrency</b>	Scan while printing or while it is transferring scan to network or fax jobs
<b>Scan Features</b>	<p>Mixed size originals  Edge erase  Reduction/enlargement  Fit to size  Scan build job  Compression Quality / File Size Control  Original type (photo and text, photo, text)  Auto background and shadow suppression  Job Flow Sheets  Scan to USB  Preview scan job</p>
<b>INPUT SPEED</b>	
<b>Resolution</b>	<p>600 x 600 dpi  400 x 400 dpi  300 x 300 dpi  200 x 200 dpi</p>
<b>Maximum Scan Area</b>	Originals up to 11 x 17 in. / A3
<b>File Formats</b>	<p>PDF Image Only  PDF  Searchable PDF  (Linearized)  PDF (A-1)  TIFF V6  XPS</p>
<b>Document Management Fields (Metadata)</b>	<p>One to six user-programmable metadata fields per scan job  Customized fields viewed on user interface  Variable data entered using virtual keyboard</p>

<b>Scan Features</b>	<p>Scan to Home                  Scan to Desktop WIA                  Scan to Desktop TWAIN                  Scan to Mailbox                  Scan to FTP                  Scan to sFTP (via EIP solution)                  Scan via SMB                  Scan via HTTP                  Scan via HTTPS                  Scan to USB Storage Device                  Scan to Fax Server</p>
<b>Supported Scan Destinations</b>	<p>Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Text searchable PDF, PDF/A, XPS, Thumbnail Preview</p>
<b>Scan to Email Features</b>	<p>Color scanning, Auto Color, Grayscale, Black-and-white                  Direct document email from device                  Manual or directory Exchange / Notes / LDAP address searching                  Signing and encryption                  Email over SSL                  Preview scan job</p>
<b>Authentication</b>	<p>SMTP authentication, POP before SMTP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)                  Scanning Security-TLS</p>
<b>FAX (OPTIONAL) – ONE OR THREE LINE FAX OPTIONS</b>	
<b>Maximum Scan Area</b>	<p>11 x 17 in. SEF</p>
<b>Fax Features</b>	<p>iFax                  Lan Fax                  IP Fax (optional)                  Fax Forward to Email                  Fax Forward to FTP destination                  Fax Forward to SMB destination                  Fax Forward to Fax destination</p>
<b>DEVICE MANAGEMENT</b>	
<b>XEROX® Embedded Web Server – INTEGRATED WEB PAGES PROVIDED BY THE DEVICE</b>	
<b>Device Status</b>	<p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul>
<b>Job Submission</b>	<p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS                  Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination)                  Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p>
<b>Device Administration</b>	<p>Allows simple, remote installation setting of configuration options and management of the device</p>
<b>Browsers</b>	<p>Internet Explorer                  Safari                  Mozilla Firefox                  Opera                  Chrome</p>
<b>Support</b>	<p>Install print/scan drivers and online support available via web page</p>
<b>Languages Supported</b>	<p>International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Polish</p>

<b>REMOTE SERVICES</b>	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>SECURITY</b>	
<b>Features</b>	<ul style="list-style-type: none"> <li>Access Controls</li> <li>AES 256-bit Encryption</li> <li>Audit Log</li> <li>Certificate Revocation List (CRL)/Status Protocol (OCSP)</li> <li>Detection of External Program Falsification (XCP Plug-in)</li> <li>Domain Filtering</li> <li>FIPS 140-2</li> <li>Firmware Verification</li> <li>Immediate Disk Overwrite</li> <li>IP Address Filtering</li> <li>IPsec</li> <li>Network Authentication</li> <li>Pre-installed Self-Signed Certificates</li> <li>Role Based Permissions</li> <li>Secure Print</li> <li>Security Certificate Management</li> <li>Smart Card Enablement (CAC/PIV/.NET)</li> <li>SNMPv3</li> <li>TLS/SSL (TLS 1.0, 1.1, 1.2)</li> <li>SIPRnet</li> </ul>
<b>PRINT SERVER</b>	
<b>XEROX® INTEGRATED COLOR SERVER</b>	
<b>Processor</b>	1.6 GHz Dual-core
<b>Memory</b>	4 GB system plus 1 GB page memory
<b>System Disk</b>	320 GB Hard Disk Drive
<b>Display</b>	10.4 in. color touchscreen flat-panel
<b>Device Operating System</b>	Linux
<b>PDLs Page Description Languages</b>	<ul style="list-style-type: none"> <li>Adobe® PostScript® 3™</li> <li>PDF</li> <li>PCL® 5c, 6</li> <li>XML Paper Specification (XPS®) (optional)</li> </ul>
<b>Print Drivers Supported</b>	Please refer to <a href="http://www.xerox.com/support">www.xerox.com/support</a> for specifics. As new operating system versions are added, support is also added for the Xerox® PrimeLink C9065/C9070 Printer. Also note that there is more than one print driver based on the configuration purchased (e.g., digital front ends, Xerox® Global Print Driver)
<b>Features</b>	<ul style="list-style-type: none"> <li>Automatic two-sided</li> <li>Bi-directional print drivers provide device and job status</li> <li>Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print)</li> <li>Secure print</li> <li>Delay print</li> <li>Embedded web server for remote control/monitor/setup</li> <li>Enhanced gloss</li> <li>Sample set</li> <li>Booklet creation</li> <li>Cover selection</li> <li>Paper selection by attribute</li> </ul>

# Xerox® PrimeLink® C9065/C9070 Printer

	<p>N-up Watermarks Banner sheets Banner printing Fit to new paper size Output tray selection Print calibration (with EFI) Print from USB (No Print Driver required)</p>
<b>Connectivity</b>	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
<b>ADDITIONAL PRINT SERVER OPTIONS</b>	
<b>XEROX® EX-C C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	AMD® GX-424CC processor 2.4 GHz
<b>Memory</b>	2 GB RAM
<b>Hard Drive</b>	500 GB
<b>Server Operating System</b>	Linux®
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and Microsoft® native formats via Fiery® Hot Folders
<b>Features</b>	<p>Easy-to-use color adjustment tools that deliver outstanding color quality from all applications and file formats.</p> <ul style="list-style-type: none"> <li>• Print logo and corporate colors correctly (including PANTONE colors)</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost-effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Fully integrated with Xerox® ConnectKey® Apps</li> <li>• Paper Catalog</li> <li>• Command WorkStation</li> <li>• Fiery Freeform</li> <li>• Fiery Remote Scan</li> </ul>
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
<b>Additional Options</b>	<ul style="list-style-type: none"> <li>• Options Bundle <ul style="list-style-type: none"> <li>– Fiery Spot-On™ with PANTONE approved libraries</li> <li>– Fiery Hot Folders</li> <li>– Fiery Virtual Printers</li> <li>– Auto Trapping</li> </ul> </li> <li>• Color Profiler Suite (with ES2000)</li> <li>• Network Hub Kit</li> <li>• Spot On</li> <li>• Hot Folders/ Virtual Printers</li> </ul>
<b>XEROX® EX-I C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	Intel Core i3-6100 (3.7 GHz) Processor (Performance optimized by proprietary combination of EFI Technology, VX600 ASIC and software)
<b>Memory</b>	4 GB
<b>Hard Drive</b>	500 GB
<b>Server Operating System</b>	Linux®
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and Microsoft® native formats via Fiery® Hot Folders

# Xerox® PrimeLink® C9065/C9070 Printer

<b>Features</b>	<ul style="list-style-type: none"> <li>• Productivity starts with a fast RIP. The Integrated Fiery Color Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and color-critical PDFs accurately and quickly</li> <li>• Fully integrated with Xerox® ConnectKey® Apps</li> <li>• Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers</li> <li>• Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the preset drivers configured for the task.</li> <li>• Get the color right. Produce precise, exact color from all applications, platforms and formats with Fiery color management tools</li> <li>• Turn up the impact with variable information. Customize your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Color Server's basic variable data printing capabilities</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost-effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Command WorkStation</li> <li>• Fiery JDF</li> <li>• Secure Erase</li> <li>• Paper Catalog</li> <li>• Fiery Compose</li> <li>• Fiery Remote Scan</li> </ul>
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
<b>Additional Options</b>	<ul style="list-style-type: none"> <li>• Productivity Package               <ul style="list-style-type: none"> <li>– Fiery ImageViewer</li> <li>– Fiery Image Enhance Visual Editor</li> <li>– Control Bar Builder</li> <li>– Postflight Report</li> <li>– Configurable Auto Trapping</li> <li>– Paper Simulation</li> <li>– Graphic Arts Filters for Hot Folders</li> <li>– Rush Print, Schedule Print and Print/Process Next</li> <li>– Fiery JobFlow Base</li> </ul> </li> <li>• Fiery impose</li> <li>• Color Profiler Suite (with ES2000)</li> <li>• Network Hub Kit</li> </ul>
	For more information, go to <a href="http://www.xerox.com">www.xerox.com</a>
<b>XEROX® EX C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	Intel® Core™ i5-6500 Processor (3.2 up to 3.6 GHz with Turbo), Quad Core
<b>Memory</b>	8 GB
<b>Hard Drive</b>	1 TB
<b>Server Operating System</b>	Windows 10
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 3, Adobe PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, Microsoft® native formats via Fiery® Hot Folders and Adobe PDF Print Engine (APPE)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Job-based Calibration Integration               <ul style="list-style-type: none"> <li>– Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colors – Color Modes for professional proofing and enhanced production color requirements – Maximum print density</li> </ul> </li> <li>• Fully integrated with Xerox ConnectKey® Apps</li> <li>• Fiery technology increases your profits by delivering high-impact documents with vibrant images and color that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production</li> </ul>

Xerox® PrimeLink® C9065/C9070 Printer

	<ul style="list-style-type: none"> <li>• The Fiery Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface. Simplify your labor-intensive document composition and imposition tasks even more by using Fiery SeeSequence Impose and Compose’s intuitive interface</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost-effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Paper Catalog</li> <li>• Sequential Printing</li> <li>• Fiery JDF</li> <li>• Insert Tabs</li> </ul>
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
<b>Additional Options</b>	<ul style="list-style-type: none"> <li>• Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs</li> <li>• Fiery Color Profiler Suite (optional) creates, verifies and edits color profiles with a single profiling solution</li> <li>• Furniture Kit – Monitor, Keyboard, and Mouse</li> <li>• Color Profiler Suite (with ES2000)</li> <li>• Removable HDD</li> <li>• Network Hub Kit</li> </ul>
	For more information, go to <a href="http://www.xerox.com">www.xerox.com</a>

# Xerox® PrimeLink® C9065/C9070 Printer

SUPPLIES		YIELD	PART NUMBER
<b>Toner Cartridges</b> (Metered)	Black	30,000 pages <sup>4</sup>	006R01521
	Cyan	34,000 pages <sup>4</sup>	006R01524
	Magenta	32,000 pages <sup>4</sup>	006R01523
	Yellow	34,000 pages <sup>4</sup>	006R01522
<b>Toner Cartridges (Sold)</b>	Black	30,000 pages <sup>4</sup>	006R01734 (NASG,ESG) 006R01738 (DMO)
	Cyan	34,000 pages <sup>4</sup>	006R01737 (NASG, ESG) 006R01741 (DMO)
	Magenta	32,000 pages <sup>4</sup>	006R01736 (NASG, ESG) 006R01740 (DMO)
	Yellow	34,000 pages <sup>4</sup>	006R01735 (NASG, ESG) 006R01739 (DMO)
<b>Black Drum Cartridge</b>	1 Cartridge	190,000 pages <sup>4</sup>	013R00663
<b>Color Drum Cartridge</b>	1 Cartridge per Color	85,000 pages <sup>4</sup>	013R00664
<b>Charge Corotron</b>	For Black Drum	190,000 pages <sup>4</sup>	013R00650
<b>Fuser</b>	110V	200,000 pages <sup>4</sup>	008R13102
	220V	200,000 pages <sup>4</sup>	008R13065
<b>Waste Toner Container</b>	1 Cartridge	50,000 pages <sup>4</sup>	008R12990
<b>Feed Roll Kits</b>	1 Assembly	300,000 pages <sup>4</sup>	008R13169

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% black-and-white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

Learn more at [www.xerox.com/PrimeLink](http://www.xerox.com/PrimeLink)

©2020 Xerox Corporation. All rights reserved. Xerox®, ConnectKey®, Global Print Driver®, PrimeLink®, SquareFold® and Xerox Extensible Interface Platform® and are trademarks of Xerox Corporation in the United States and/or other countries. EFI, Splash, Fiery® and RPX-iii are trademarks of Electronics for Imaging, Inc. Product appearance, build status and/or specifications are subject to change without notice.  
02/20 PN03335\_T91 BR27331 PC95S-01UB